

D725



USB port



Power over Ethernet



IPv6 & IPv4



Gigabit Ethernet



Expansion module connectable



Headset connectable



Security (TLS & SRTP)

Benefits

- Backlit graphical display, 4 lines
- Dual-angle footstand: 46° and 28°
- Wallmountable
- Wideband hands-free talking (speakerphone)
- Digital Signal Processor (DSP) enhanced audio quality
- 2-port 1-Gigabit Ethernet switch (RJ45) IEEE 802.3
- Power over Ethernet IEEE 802.3af, Class 2
- USB headset-ready⁽¹⁾
- D7 expansion module-ready⁽¹⁾
- Support for USB WiFi stick (RT2070/RT3070 chipsets)⁽¹⁾
- Support for wireless headsets via electronic hook switch (EHS)⁽¹⁾

Firmware

Features

- 12 SIP identities / accounts
- XML browser
- Call lists for dialed, received, missed calls
- Local directory with 1000 entries
- Multiple language support
- DTMF in-band / out-of-band / SIP-INFO
- Interoperable with all major IP-PBX platforms

Call Features

- Speed dialing
- URL dialing
- Local dial plan
- Automatic redial on busy
- Call completion (busy/unreachable)⁽³⁾
- Caller identification
- Call waiting
- Call blocking (deny list)
- Auto answer
- Hold
- Music on hold⁽³⁾
- Handling of up to 12 simultaneous calls
- Blind and attended transfer
- Call forwarding
- 3-way conferencing on the phone
- Extension monitoring, call pickup⁽³⁾
- Call park, call unpark⁽³⁾
- Multicast paging
- DND mode (do not disturb)
- Keyboard lock
- Client matter code (CMC)³⁾
- Unified communications ready

Audio

- Codecs:
 - G.711 A-law, μ -law
 - G.722 (wideband)
 - G.726, G.729AB, GSM 6.10 (FR)
- Built-in assignable ringtones
- Comfort noise generator (CNG)
- Voice activity detection (VAD)

Set-Up

- Configurable through web interface
- Provisioning:
 - Automatic loading of settings via HTTP/HTTPS/TFTP
 - DHCP Options 66/67
 - Snom Redirection Service
 - Remote management via TR-069 / TR-111

Specification

Protocols

- SIP (RFC3261)
- DHCP, NTP
- HTTP / HTTPS / TFTP
- LDAP (Directory)
- Dual Stack IPv4 / IPv6

User Interface

- Localization (language, time, dial tone)
- Red LED for call indication / message waiting
- 4 context-sensitive keys
- 18 programmable line / function keys with multicolor LEDs
- Paper inlay for labeling of function keys
- Dedicated keys for: Message, DND, directory, menu, transfer, hold
- Audio keys with LED indication: Mute, speakerphone, headset
- Volume key
- 4-way navigation key, OK and cancel keys
- Menu-driven user interface

Security

- 802.1X Authentication and EAPOL
- Transport layer security (TLS)
- SRTP (RFC3711), SIPS, RTCP
- HTTPS server/client
- Password-protected web interface
- VPN support
- VLAN (IEEE 802.1Q)
- LLDP-MED, RTCP-XR

Phone Features

- Dimensions (approx.):
 - 238 x 190 x 40 mm (LxWxD) w/o foot stand
 - 238 x 190 x 200/220 mm (LxWxD) with foot stand
- Weight (approx.): device 670g, footstand 230g
- Input voltage: 5V DC (SELV)
- Power supply: PoE or power adapter 5V DC 10 W⁽²⁾
- Handset: 4P4C connector
- Headset connectors:
 - Wired: 4P4C connector or USB connector
 - Wireless: USB connector or proprietary snom 4-pin connector for snom EHS Advanced⁽¹⁾
- Hearing aid compatible (HAC) handset
- 1 x USB 2.0 host port, Type A, Hi/Full/Low-Speed
- Environmental conditions:
 - Ambient temperature: 0°C to 35°C (32°F to 95°F)
 - Storage temperature: -10°C to 45°C (14°F to 113°F)
 - Humidity: 5% to 95% (non-condensing)
- Included in delivery:
 - Base phone unit
 - Footstand
 - Handset with cord
 - Ethernet cable
 - Quick Start Guide
- Color: Black
- **Part Number: 00003916** (all markets)

Type Approval

- CE Mark
- FCC Class B
- Safety IEC 60950, CB

⁽¹⁾ Optional accessory (see below for part numbers)

⁽²⁾ Sold separately

⁽³⁾ If supported by PBX

Part numbers for optional accessories

- 00004011 D7 Expansion Module (black)
- 00004325 Power Adapter A6 with EU clip
- 00004326 Power Adapter A6 with US clip
- 00001168 UK clip for Power Adapter A6
- 00001167 AUS clip for Power Adapter A6
- 00004394 Snom Power Adaptor 10W
- 00002362 Snom EHS Advanced
- 00004341 Monaural Headset Snom A100M
- 00004342 Binaural Headset Snom A100D

Series Overview



On the internet

<https://www.snom.com/d725/>