

# Snom MeetingPoint

Share your vision



## Snom MeetingPoint



### Key Features

- OmniSound® full duplex wideband sound technology
- 3-way conference calls
- Recording of up to 10 persons depending on size of the room
- Simultaneous management of internal and external telephone listings (LDAP)
- Extra microphone connection for wider reception
- 12 SIP registrations
- Open VPN

The first VoIP conference telephone from Snom, the Snom MeetingPoint, is the ideal complement for everyone who frequently needs to make multi-location arrangements. With the MeetingPoint, up to two parties can join a conference call from different locations helping your company cut costs and save time!

Of course, the Snom MeetingPoint provides the additional comfort, that you would expect from snom: management of up to two external participants, LDAP, contact listings, excellent sound by OmniSound® 2.0 etc.

The snom MeetingPoint is perfectly qualified for use in medium to large conference rooms. Thanks to its reliable suppression of disturbing background noise and its excellent sound quality you can hold your telephone conferences with large groups of up to 10 persons (depending on size of the room) without adversely affecting the intelligibility of the call.

Three speakers, equipped with full duplex wideband audio (G.722), provide balanced and full sound which Snom customers already know from the Snom desktop telephone handset. The integrated special microphones ensure that your interlocutors feel as if you are sitting in the neighboring office - and not on the other side of the world!

The graceful styling of the Snom MeetingPoint integrates ideally into your VoIP infrastructure and makes it a subtle eye-catcher for your conference room.

## General Features

- Size: Diameter: 240 mm, Height: 77 mm
- Display: Backlit graphical LCD, 128x64 pixels
- Weight: 1 kg
- Colour: black
- Keypad: Alphanumeric 0-9, \*, #, dial, hang up, mute, menu, conference, recording, volume control, 5 context sensitive keys
- Microphone: circular (360°) recording characteristics
- Reception range: < 20 persons (depending on size of the room)
- Speaker: Frequency range: 150-15000 Hz playback
- Volume: 90 db SPL 0.5m. Equalizer function
- Anti-theft protection: Kensington security slot

## Connections

- Network connection: 1x RJ-45, PoE 10/100MBit
- Power supply: 100-240 V AC/14 V DC - PoE
- Additional microphones: modular 2/2

## Environmental conditions

- Temperature: 5°-40° C
- Humidity: 20-80%.
- Recommended acoustic room conditions:
  - Reverberation time: 0.5 S Rt 60
  - Background noise: 45 dbA

## Type Approvals

- CE marking
- Safety IEC 60950