

Deskphone Comparison List

Deskphones (Waranty 3 Years)

| Funktionen /Telefon | D120 | D305 | D315 | D335 | D345 | D375 | D385 |
|---|---|---|---|---|---|---|---|
| Image |  |  |  |  |  |  |  |
| Display | Hi-Res Grafik | Hi-Res S/W 3.2" | Hi-Res S/W 3.2" | Hi-Res TFT-color 2.7" | Grafik 4" | Hi-Res TFT-color 4.3" | Hi-Res TFT-color 4.3" |
| Display inclination | fixed | fixed | fixed | fixed | Variable in 6 steps | Variable in 6 steps | Variable in 6 steps |
| Main Display | 132 x 64px | 300 x 100px | 300 x 100px | | 384 x 128px | 480 x 272 px | 480 x 272 px |
| • Backlight | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| 2nd Display | - | - | - | - | 254 x 100px | - | 254 x 100px |
| Position | 36° | Flat angle | Flat angle | Flat angle | Flat angle | Flat angle | Flat angle |
| Sip identities | 2 | 4 | 4 | 12 | 12 | 12 | 12 |
| Color | Black | Black-Blue | Black-Blue | Black-Blue | Black-Blue | Black-Blue | Black-Blue |
| Artikelnummer Black | 00004361 | 00004257 | 00004258 | 00004390 | 00004260 | 00004141 | 00004340 |
| Artikelnummer White | | | | | | | |
| Programmable keys / LEDs | | | | | | | |
| BLF Tasten | 2 (single color) | 5 (single color) | 5 (single color) | 8/32 (multi color) | 12/48 (multi color) | 12 (multi color) | 12/48 (multi color) |
| Call indicator | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Message LED | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Connectors | | | | | | | |
| Ethernet - 2 Port | 10/100 Mbit | 10/100 Mbit | Gigabit | Gigabit | Gigabit | Gigabit | Gigabit |
| Handset | 1 x 4P4C | 1 x 4P4C | 1 x 4P4C | 1 x 4P4C | 1 x 4P4C | 1 x 4P4C | 1 x 4P4C |
| Headset | 1 x 4P4C | 1 x 4P4C | 1 x 4P4C | 1 x 4P4C | 1 x 4P4C | 1 x 4P4C | 1 x 4P4C |
| EHS | ✗ | ✓ (RJ12) | ✓ (RJ12) | ✓ (RJ12) | ✓ (RJ12) | ✓ (RJ12) | ✓ (RJ12) |
| Part.No. 00002362 | | | | | | | |
| USB | ✗ | ✗ | ✓ (1x) | ✓ (1x) | ✓ (1x) | ✓ (1x) | ✓ (1x) |
| Power Jack | 5 volts 2mm | 5 volts 2mm | 5 volts 2mm | 5 volts 2mm | 5 volts 2mm | 5 volts 2mm | 5 volts 2mm |
| Exp Module (USB) | | | | | | | |
| • D3 - 00004327 | ✗ | ✗ | ✓ up to 3 | ✓ up to 3 | ✓ up to 3 | ✓ up to 3 | ✓ up to 3 |
| • D7 - Black: 00004011 White: 00004382 | | | | | | | |
| Interfaces | | | | | | | |
| PoE IEEE 802.3af - Class | 1 | 1 | 2 | 2 | 3 | 3 | 3 |
| Bluetooth | ✗ | ✗ | optional via USB | optional via USB | optional via USB | integrated (BT4.0) | integrated (BT4.0) |
| Wi-Fi | ✗ | ✗ | optional via USB | optional via USB | optional via USB | optional via USB | optional via USB |
| Features /Phones | D120 | D305 | D315 | D335 | D345 | D375 | D385 |
| Dimensions: | | | | | | | |
| • Without foot stand (LxWxD) mm | 205x161x32 | | | | | | |
| • With foot stand (LxWxD) mm | 205x161x120 | 185x200x120 | 185x200x120 | 198x198x120 | 250x185x120 | 250x200x135 | 250x185x120 |
| Weight: (total) | 620 | 720g | 720g | 800g | 880g | 900g | 880g |

| | | | | | | | |
|---|------------------|---|---|---|---|---|---|
| • Snom Redirection Service / SRAPS | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| • Remote management via TR-069 / TR-111 | ✓ TR-069 only | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| • Plug & Play (PnP) | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |

Call features

| | | | | | | | |
|---|------|------|------|----|------|------|------|
| Speed dialing | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| URL dialing | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Local dial plan | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Automatic Redial on Busy | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Call completion (busy /unreachable) | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Caller identification | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Call waiting | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Call blocking (deny list) | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Auto answer | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Hold | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Music on hold | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Handling of simultaneous calls up to | 2 | 4 | 4 | 12 | 12 | 12 | 12 |
| Blind and attended transfer | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Call forwarding | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| 3-way conference on the phone | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Extension monitoring, call pickup | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Call park, call unpark | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Multicast paging | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| DND mode (do not disturb) | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Keyboard lock | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Client matter code (CMC) | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Unified communicat. ready | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Blocking of anonymous calls | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Call History: Lists of missed, received and dialed calls | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Features/Phones | D120 | D305 | D315 | | D345 | D375 | D385 |

Environmental Conditions

| | | | | | | | |
|---------------------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| Temperature | | | | | | | |
| • Ambient | 0°C to 35°C | 0°C to 35°C | 0°C to 35°C | 0°C to 35°C | 0°C to 35°C | 0°C to 35°C | 0°C to 35°C |
| • Storage | -10°C to 45°C | -10°C to 45°C | -10°C to 45°C | -10°C to 45°C | -10°C to 45°C | -10°C to 45°C | -10°C to 45°C |
| Humidity (non-condensing) | 5% to 95% | 5% to 95% | 5% to 95% | 5% to 95% | 5% to 95% | 5% to 95% | 5% to 95% |

Homologation

| | | | | | | | |
|-------------------|---|---|---|---|---|---|---|
| Type approval | | | | | | | |
| • CE Mark | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| • Safety EN 60950 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |